

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name

Bauder LiquiPAVE R WI 10 kg

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	grout resin
Recommended restrictions	Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company designation	Bauder Ltd. 70 Landseer Road
	Ipswich IP3 0DH Telephone: +44 (0)1473 257671
E-mail (competent person)	info@bauder.co.uk

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only). For medical advice, members of the public should contact NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

2.2 Label elements

Hazard pictogram

GHS02


Danger



Signal word

Hazardous component(s) to be indicated on label

H-statement(s)



H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

Article-No.: GB81002015 Revision date: 11.03.2022 Version: 2.0/en



P-statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P312: Call a POISON CENTER/doctor if you feel unwell.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization

Mixture with reactive acrylates

Hazardous ingredients

Ingredient Numbers		Classification (EC) 1272/2008	Concentration
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6REACH No.: 01-2119452498-28-XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1;H317	35.0 - 40.0 % by weight
2-ethylhexyl acrylate	CAS No.: 103-11-7 EC-No.: 203-080-7 Index-No.: 607-107-00-7REACH No.: 01-2119453158-37-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	20.0 - 25.0 % by weight
aliphatic urethanacrylate		Skin Irrit. 2; H315 Eye Irrit. 2; H319	5.0 - 10.0 % by weight
2,2'-ethylenedioxydiethyl dimethacrylate	CAS No.: 109-16-0 EC-No.: 203-652-6REACH No.: 01-2119969287-21-XXXX	Skin Sens. 1; H317	1.0 - 5.0 % by weight
1,1`-(p-Tolylimi- no)dipropan-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1REACH No.: 01-2119980937-17-XXXX	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Move out of dangerous area. Take off all contaminated clothing immediately. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.		
If inhaled	Move to fresh air. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.		
In case of skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation occurs, seek medical advice/attention.		



In case of eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO2), Foam, Water spray, Dry powder
Extinguishing media which mustnot	High volume water jet
be used for safety reasons	

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases	Hazardous decomposition products formed under fire conditions. Violent polymerization may be caused by: Extremes of temperature anddirect sunlight.
5.3 Advice for firefighters	In the event of fire, wear self-contained breathing apparatus.
Special protective equipment for	
firefighting	Fire residues and contaminated fire extinguishing water must be dis- posed of
Additional information on fire-	in accordance with local regulations. Do not allow run-off fromfire fighting to
fighting	enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment. Ensure adequate ventilation. Vapours are heavier than air and mayspread along floors.
6.2 Environmental precautions	S
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into sur- face water or sanitary sewer system. Avoid subsoil penetration.
6.3 Methods and material for o	containment and cleaning up
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean contaminated surface thoroughly.
6.5 Additional information	
Other information	Treat recovered material as described in the section "Disposal considerations".



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	Handle and open container with care. Avoid contact with skin and eyes. Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty container away from heat and sources of ignition.
Precautions	Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.Observe label precautions.
Advice on protection against fireand explosion	Take precautionary measures against static discharges. Vapours may form explosive mixture with air. Use water spray to cool unopened containers.
7.2 Conditions for safe storage	e, including any incompatibilities
Storage space and container	Keep in properly labelled containers. Containers which are opened mustbe

Storage space and container	Keep in properly labelled containers. Containers which are opened mustbe
requirements	carefully resealed and kept upright to prevent leakage.
	Store in accordance with the particular national regulations. Keep in acool, well-ventilated place.
TRGS 510	3

Recommended storage temperature Keep in a dry, cool place.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Great Britain Long-term exposure value/ ppm		-term exposu e/ mg/m3	re Short-term value / ppr	-	Short-term expos value / mg/m3	sure	Source
50 208			100		416		EH40/2005 Workplace exposure limits (2011)
Europe							
Long-term exposure	value/	Short-term e ppm	xposure value /	Issuing da	te	Sour	ce
50		100		2009/161 DIREC		CTIVE 2009/161/EU	
DNEL	Targe	et group	Exposure	oute	Exposure frequen	icy	Source
210 mg/m ³	Work	ers	Inhalation		Long term effects Lo	ocal	Company data
210 mg/m ³	Work	ers	Inhalation		Long term effects systemic		Company data
1,5 mg/cm ²	Work	ers Skin			Long term effects Local		Company data
13,67 mg/kg	Work	ers	Skin		Long term effects systemic		Company data
		umers	Inhalation		Long term effects Lo		Company data

Commercial Product Name: Bauder LiquiPAVE R WI 10 kg Article-No.: GB81002015 Revision date: 11.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

BAUDER

74,3 mg/m ³	Consumers	Inhalation	Long term effects, systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Long term effects Local	Company data
8,2 mg/kg	Consumers	Skin	Long term effects systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Short-term effects Local	Company data

PNEC	Exposure route	Source
0,94 mg/l	freshwater	Company data
0,094 mg/l	marine water	Company data
5,74 mg/kg	sediment	Company data
1,47 mg/kg	Soil	Company data

2-ethylhexyl acrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
37,5 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Short-term effects Local	Company data
4,5 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data

PNEC	Exposure route	Source
0,002752 mg/l	fresh water	Company data
0,000272 mg/l	seawater	Company data
2,3 mg/l	wastewater treatment plant	Company data
0,126 mg/kg	sediment Water	Company data
0,126 mg/kg	sediment seawater	Company data
1,0 mg/kg	Soil	Company data
0,0023 mg/kg	Intermittent release.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
48,5 mg/m ³	Workers	Inhalation	Long term effects systemic	Company data
13,9 mg/kg	Workers	dermal exposure	Long term effects systemic	Company data
14,5 mg/m ³	Consumers	Inhalation	Long term effects systemic	Company data
8,33 mg/kg	Consumers	dermal exposure	Long term effects systemic	Company data
8,33 mg/kg	Consumers	Oral	Long term effects systemic	Company data

PNEC	Exposure route	Source
0,164 mg/l	freshwater	Company data
0,274 mg/kg	Soil	Company data
0,185 mg/kg	marine sediment	Company data
1,85 mg/kg	freshwater sediment	Company data
10 mg/l	Waste water treatment	Company data
0,164 mg/l	intermittent releases	Company data
0,00164 mg/l	marine water	Company data



1,1`-(p-Tolylimino)dipropan-2-ol

DNEL	Target group	Exposure route	Exposure frequency	Source
2 mg/m ³	Workers	Inhalation	Long term effects	Company data
0,6 mg/kg	Workers	Skin	Long term effects	Company data

PNEC	Exposure route	Source
199,5 mg/l	Waste water treatment	Company data
0,0072 mg/kg	marine water	Company data
0,017 mg/l	freshwater	Company data

8.2 Exposure controls

Respiratory protection	In interiors and during exceeding of the air limit values carrying of protective masks is absolutely necessary. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposurelimit they must use appropriate certified respirators.
Remarks	Recommended Filter type: A1, A2 (in case of higher concentration)
Hand protection	Protective gloves complying with EN 374.Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Unsuitable material	woven fabric, Leather gloves
Suitable material	Nitrile
Eye protection	Tightly fitting safety goggles
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and at the end of workday. Use protective skin cream be-fore handling the product. Avoid contact with the skin and the eyes.
Engineering measures	Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state

liquid



Form	Liquid
Colour	milky
Odour	smell of Methylmethacrylate
рН	not applicable
Melting point [°C] / Freezing point[°C]	not determined
Boiling point [°C]	> 100 °C
Flash point [°C]	10 °C
Evaporation rate [kg/(s m ²)]	not determined
Explosion limits [Vol-%]	The product itself has not been tested. methyl methacrylate
Lower limit	1,7 vol. %
Upper limit	12,5 vol. % 2-ethylhexyl acrylate
Lower limit	0,9 vol. %
Upper limit	6,4 vol. %
Vapour pressure [kPa]	not determined
Vapour density	not determined
Density [g/cm ³]	0,98 g/cm ³
Temperature [°C]	20 °C
Water solubility [g/l]	
Remarks	insoluble
Partition coefficient n-octanol /wa-ter (log P O/W)	not determined
Autoignition temperature [°C]	not determined
Explosive properties	Not relevant In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	Not relevant
9.2 Other information	
Ignition temperature [°C]	not determined
Flow time [s]	55 sec
Temperature [°C]	20 °C
Measuring method	DIN cup 6 mm



SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution. Risk of receptacle bursting.

10.4 Conditions to avoid

Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid

Reacts violently with peroxides. Reducing agents, Strong bases, Amines, Oxidizing agents

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

Hazardous ingredients

methyl methacrylate				
Value	Test criterion	Test species	Measuring method	Source
>5000 mg/kg	LD50	rat	OECD Test Guideline 401	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
4435 mg/kg	LD50	rat	Company data

aliphatic urethanacrylate				
Value	Test criterion	Test species	Source	
>2001 mg/kg	LD50	rat	Company data	

2,2'-ethylenediox	kydiethyl dimethacryla	ite		
Value	Test criterion	Test species	Remarks	Source
10066 mg/kg	LD50	rat	* 1)	Company data

* 1): Information given is based on data on the components and the toxicology of similar products.

1,1`-(p-Tolylimino)dipropan-2-ol			
Value	Test criterion	Test species	Source
45 mg/kg	LD50	rat	Company data

Dermal toxicity [mg/kg]

Hazardous ingredients

methyl methacrylate

Commercial Product Name: Bauder LiquiPAVE R WI 10 Article-No.: GB81002015 Revision date: 11.03.2022 Version: 2.0/en



making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

Value	Test criterion	Test species	Source
>5000 mg/kg	LD50	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
7522 mg/kg	LD50	rabbit	Company data

2,2'-ethylenedioxydiethyl dimethacrylate			
Value	Test criterion	Test species	Source
>2001 mg/kg	LD50	mouse	Company data

1,1`-(p-Tolylimino)dipropan-2-ol			
Value	Test criterion	Test species	Source
2001 mg/kg	LD50	rat	Company data

Inhalative toxicity [mg/l]

Hazardous ingredients

2-ethylhexyl acrylate		
Value	Test species	Source
1,19 mg/l	rat	Company data

LC50 Inhalation 4h for vapours [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test criterion	Test species	Source
29,8 mg/l	LC50	rat	Company data

Irritant effect on skin

methyl methacrylate		
Value	Test species	Source
irritating	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test species	Exposure duration	Source
		[h]	
Skin irritation	rabbit	4 h	Company data

aliphatic urethanacrylate	
Value	Source
May cause skin irritation.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
No skin irritation	Company data

Commercial Product Name: Bauder LiquiPAVE R WI 10 Article-No.: GB81002015 Revision date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No skin irritation	Company data

Irritant effect on eyes

Hazardous ingredients			
methyl methacrylate			
Value	Test species	Source	
Irritant	rabbit	Company data	

2-ethylhexyl acrylate			
Value	Measuring method	Test species	Source
slightly irritating	OECD Test Guideline 405	rabbit	Company data

aliphatic urethanacrylate	
Value	Source
Causes serious eye irritation.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
No eye irritation	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Irritant	Company data

Sensitization

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
Skin sensitization	mouse	Company data

2-ethylhexyl acrylate	
Value	Source
Skin sensitization	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
Skin sensitizer	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No sensitization responses were observed.	Company data

Carcinogenic effects

Article-No.: GB81002015 Revision date: 11.03.2022 Version: 2.0/en Replaces version from: 21.09.2018 Print date: 11.03.2022

methyl methacrylate		
Value	Test species	Source
not a carcinogen	rat, mouse	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
No known effect.	Company data

Mutagenicity

Hazardous ingredients	
methyl methacrylate	
Value	Source
not mutagenic	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
No known effect.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
negative	Company data

Reproduction toxicity

Hazardous ingredients

methyl methacrylate	
Value	Source
not toxic to reproduction	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
No known effect.	Company data

Specific target organ toxicity (single exposure) [mg/kg]



making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

methyl methacrylate	
Value	Source
Causes respiratory tract irritation.	Company data

2-ethylhexyl acrylate	
Value	Source
Causes respiratory tract irritation.	Company data

Specific target organ toxicity (repeated exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
No known effect.	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
No known effect.	Company data

11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes, respiratory system and skin. Irritatingto mucous membranes

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

methyl meth	methyl methacrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source		
191 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data		

2-ethylhexyl acrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source	

Commercial Product Name: Bauder LiquiPAVE R WI 10 k Article-No.: GB81002015 Revision date: 11.03.2022 Version: 2.0/en



making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

1,81 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data
-----------	------	--	---------------------------	------	--------------

2,2'-ethylenedioxydiethyl dimethacrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source	
16,4 mg/l	LC50	Brachydanio rerio (zebra fish)	OECD Test Guideline203	96 h	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure dura- tion [h]	Source	
17 mg/l	LC50	Brachydanio re- rio (zebra fish)	96 h	Company data	

Toxicity to daphnia [mg/l]

methyl methacrylate						
Value	Test criteri- on	Test species	Exposure duration [h]	Measuring method	Source	
69 mg/l	EC50	Daphnia magna (Wa- ter flea)	48 h	OECD Test Guideline202	Company da- ta	

2-ethylhexyl acrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
1,3 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

aliphatic urethanacrylate						
Value	Test criterion	Test species	Source			
>100 mg/l	LC50	Daphnia magna (Water flea)	Company data			

2,2'-ethylenedioxydiethyl dimethacrylate					
Value	Test criterion	Test species	Exposure dura- tion [h]	Source	
30,2mg/l	EC50	Daphnia magna (Water flea)	21 day(s)	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure dura- tion [h]	Source	
28,8 mg/l	EC50	Daphnia magna (Water flea)	18 h	Company data	



Toxicity to algae [mg/l]

Hazardous ingredients

methyl meth	methyl methacrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
>110 mg/l	EC50	Selenastrum capricornu- tum (green algae)	72 h	OECD Test Guideline201	Company data		

2-ethylhexyl acrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
1,71 mg/l	ErC50	Desmod- esmus sub- spicatus	72 h	OECD Test Guideline201	Company data

2,2'-ethylenedioxydiethyl dimethacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
>101 mg/l	EC50	Pseudokirch- neriella sub- capitata	72 h	OECD Test Guideline201	Company data

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure dura- tion [h]	Source
245 mg/l	EC50	Desmodesmus subspicatus	27 h	Company data

NOEC (fish) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
9,4 mg/l	Brachydanio rerio (ze-	OECD Test Guideline	Company data
	bra fish)	210	

NOEC (daphnia) [mg/l] Hazardous ingredients

i la	zaidous iligieulents			
	methyl methacrylate			
	Value	Test species	Measuring method	Source
	37 mg/l	Daphnia magna (Water flea)	OECD Test Guideline 202	Company data

NOEC (algae) [mg/l]

Tiazai uous ingreulents			
2-ethylhexyl acrylate			
Value	Test species	Measuring method	Source



making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

0,45 mg/l	Desmodesmus subspi- catus	OECD Test Guideline 201	Company data
rsistence and degra adability ardous ingredients	dability		
methyl methacrylate			
Value Readily biodegradable.	Method of an OECD 301C/ IS 92/69/V, C.4-F	-	urce mpany data
2-ethylhexyl acrylate			
Value		Source	
Readily biodegradable.		Company data	
2,2'-ethylenedioxydieth	vl dimethacrylate		
Value	.y. amonaoi yiate	Source	
Readily biodegradable.		Company data	
1,1`-(p-Tolylimino)dipro	opan-2-ol		
1,1`-(p-Tolylimino)dipro Value	opan-2-ol	Source	
	opan-2-ol	Source Company data	
Value			
Value Poorly biodegradable. Oaccumulative poten imulation cardous ingredients methyl methacrylate		Company data	
Value Poorly biodegradable. Oaccumulative pote imulation cardous ingredients methyl methacrylate Value	ntial	Company data	
Value Poorly biodegradable. Oaccumulative potentiation unulation ardous ingredients methyl methacrylate Value Does not bioaccumulate. 2-ethylhexyl acrylate Value Bioaccumulation slight, log 2,2'-ethylenedioxydieth	ntial Pow 4,64	Company data Source Company data Source Company data	
Value Poorly biodegradable. Oaccumulative potential imulation cardous ingredients methyl methacrylate Value Does not bioaccumulate. 2-ethylhexyl acrylate Value Bioaccumulation slight, log 2,2'-ethylenedioxydieth Value	ntial Pow 4,64	Company data Source Company data Source Company data Source Source	
Value Poorly biodegradable. Oaccumulative poter imulation ardous ingredients methyl methacrylate Value Does not bioaccumulate. 2-ethylhexyl acrylate Value Bioaccumulation slight, log 2,2'-ethylenedioxydieth	ntial Pow 4,64	Company data Source Company data Source Company data	
Value Poorly biodegradable. Oaccumulative poter imulation cardous ingredients methyl methacrylate Value Does not bioaccumulate. 2-ethylhexyl acrylate Value Bioaccumulation slight, log 2,2'-ethylenedioxydieth Value slight	ntial Pow 4,64 nyl dimethacrylate	Company data Source Company data Source Company data Source Source	
Value Poorly biodegradable. Oaccumulative potential imulation cardous ingredients methyl methacrylate Value Does not bioaccumulate. 2-ethylhexyl acrylate Value Bioaccumulation slight, log 2,2'-ethylenedioxydieth Value	ntial Pow 4,64 nyl dimethacrylate	Company data Source Company data Source Company data Source Source	



making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

12.4 Mobility in soil

Mobility

Hazardous ingredients		
methyl methacrylate		
Mobility	Source	
Terrestrial Compartment Not relevant	Company data	

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination

Hazardous ingredients

methyl methacrylate	
Value	Source
This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

2-ethylhexyl acrylate		
Value	Source	
This substance is not considered to be persistent,	Company data	
bioaccumulating nor toxic (PBT).		

aliphatic urethanacrylate		
Value	Source	
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data	

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

12.6 Other adverse effects

Further information on ecology

We have no quantitative data concerning the ecological effects of this product.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The following Waste Codes are onlysuggestions:
Waste Code	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Uncleaned empty packaging	Empty containers should be taken for local recycling or waste disposal. Dispose of in accordance with local regulations.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.2 Description of the goods	PAINT	PAINT	PAINT
UN proper shipping name		PAINT	Paint
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group			
Labels	3	3	3
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
SP 640	640E		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		A	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to	Not relevant
Annex II of MARPOL and the IBC	
Code	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations	Additionally, observe any national regulations!
Classification in compliance withthe Industrial Safety Regulation	highly flammable
GISCODE	RMA10



SECTION 16: Other information

Relevant H-phrases	 H225: Highly flammable liquid and vapour. H300: Fatal if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H412: Harmful to aquatic life with long lasting effects. 		
Wording of the hazard classes	Flam. Liq.: Flammable liquid STOT SE: Specific target organ toxicity - single exposure Skin Irrit.: Skin irritation Skin Sens.: Skin sensitization		
	Aquatic Chronic: Hazardous to the aquatic environment		
	Eye Irrit.: Serious eye irritation Acute Tox.: Acute toxicity		
Classification for mixtures and used	Classification	Evaluation	
evaluation method according to regulation (EC) 1272/2008 [CLP]	Flam. Liq. 2; H225	Calculated	
	Skin Irrit. 2; H315	Calculated	
	Skin Sens. 1; H317	Calculated	
	STOT SE 3; H335	Calculated	
Department issuing safety data sheet	Environmental Department		
Recommended restrictions	Reserved for industrial and professional use.		

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.