SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name

Bauder LiquiBALKON WI 10 kg

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses fluid plastic sealing

Recommended restrictions Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company designation	Bauder Ltd.
	70 Landseer Road
	Ipswich IP3 0DH
	Telephone: +44 (0)1473 257671
E-mail (competent person)	info@bauder.co.uk

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only). For medical advice, members of the public should contact NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

2.2 Label elements

Hazard pictogram



Signal word

Hazardous component(s) to be indicated on label

H-statement(s)



Danger

methyl methacrylate, 2-ethylhexyl acrylate, 2,2'-[(4-methylphenyl)imino]bisethanol

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Bauder LiquiBALKON WI 10 kg Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en

Replaces version from: 21.09.2018 Print date: 11.03.2022

BAU

making roofs secure

* P-statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection.

P312: Call a POISON CENTER/doctor if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization

Mixture with reactive acrylates

Hazardous ingredients

Ingredient	Numbers	Classification (EC) 1272/2008	Concentration
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6REACH No.: 01-2119452498-28-XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1;H317	20.0 - 25.0 % by weight
2-ethylhexyl acrylate	CAS No.: 103-11-7 EC-No.: 203-080-7 Index-No.: 607-107-00-7REACH No.: 01-2119453158-37-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	10.0 - 15.0 % by weight
aliphatic urethanacrylate		Skin Irrit. 2; H315 Eye Irrit. 2; H319	5.0 - 10.0 % by weight
1,1`-(p-Tolylimi- no)dipropan-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1REACH No.: 01-2119980937-17-XXXX	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight
2,2'-[(4-methylphenyl)imi- no]bisethanol	CAS No.: 3077-12-1 EC-No.: 221-359-1 * REACH No.: 01-2120791684-40-XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Move out of dangerous area. Take off all contaminated clothing immediately. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.
If inhaled	Move to fresh air. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
In case of skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation occurs, seek medical advice/attention.

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Bauder LiquiBALKON WI 10 kg Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en

Replaces version from: 21.09.2018 Print date: 11.03.2022

In case of eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO2), Foam, Water spray, Dry powder
Extinguishing media which mustnot	High volume water jet
be used for safety reasons	

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases	Hazardous decomposition products formed under fire conditions. Violent polymerization may be caused by: Extremes of temperature anddirect sunlight.
5.3 Advice for firefighters	In the event of fire, wear self-contained breathing apparatus.
Special protective equipment for	
firefighting	Fire residues and contaminated fire extinguishing water must be dis- posed of
Additional information on fire-	in accordance with local regulations. Do not allow run-off fromfire fighting to
fighting	enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment. Ensure adequate ventilation. Vapours are heavier than air and mayspread along floors.
6.2 Environmental precaution	S
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.
6.3 Methods and material for o	containment and cleaning up
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).Clean contaminated surface thoroughly.
6.5 Additional information	
Other information	Treat recovered material as described in the section "Disposal considerations".

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	Handle and open container with care. Avoid contact with skin and eyes. Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty container away from heat and sources of ignition.
Precautions	Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.Observe label precautions.
Advice on protection against fireand explosion	Take precautionary measures against static discharges. Vapours may form explosive mixture with air. Use water spray to cool unopened containers.
7.2 Conditions for safe storag	e, including any incompatibilities

Storage space and container	Keep in properly labelled containers. Containers which are opened must be
requirements	carefully resealed and kept upright to prevent leakage.
	Store in accordance with the particular national regulations. Keep in acool, well-ventilated place.

TRGS 510

3

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

methy	I metha	crylate

Great Britain				
Long-term exposure	Long-term exposure	Short-term exposure	Short-term exposure	Source
value/ ppm	value/ mg/m3	value / ppm	value / mg/m3	
50	208	100	416	EH40/2005 Workplace
				exposure limits (2011)

Long-term expose ppm	sure value/	Short-term exposure value / ppm		Issuing	Issuing date		Source	
50		100		2009/161		DIRE	DIRECTIVE 2009/161/EU	
DNEL	Targe	et group	Exposur	e route	Exposure frequ	ency	Source	
210 mg/m ³	Work	ers	Inhalation		Long term effects	Local	Company data	
210 mg/m ³	Work	ers	Inhalation		Long term effects systemic		Company data	
1,5 mg/cm ²	Work	ers	Skin		Long term effects	Local	Company data	
13,67 mg/kg	Work	ers	Skin		Long term effects systemic		Company data	
105 mg/m ³	Cons	umers	Inhalation		Long term effects	Local	Company data	
74,3 mg/m ³	Cons	umers	Inhalation		Long term effects systemic	I	Company data	
1,5 mg/cm ²	Cons	umers	Skin		Long term effects	Local	Company data	

Commercial Product Name: Bauder LiquiBALKON WI 10 k Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

BAUDER

8,2 mg/kg	Consumers	Skin	Long term effects systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Short-term effects Local	Company data

PNEC	Exposure route	Source
0,94 mg/l	freshwater	Company data
0,094 mg/l	marine water	Company data
5,74 mg/kg	sediment	Company data
1,47 mg/kg	Soil	Company data

2-ethylhexyl acrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
37,5 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Short-term effects Local	Company data
4,5 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data

PNEC	Exposure route	Source
0,002752 mg/l	fresh water	Company data
0,000272 mg/l	seawater	Company data
2,3 mg/l	wastewater treatment plant	Company data
0,126 mg/kg	sediment Water	Company data
0,126 mg/kg	sediment seawater	Company data
1,0 mg/kg	Soil	Company data
0,0023 mg/kg	Intermittent release.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol

DNEL	Target group	Exposure route	Exposure frequency	Source
2 mg/m ³	Workers	Inhalation	Long term effects	Company data
0,6 mg/kg	Workers	Skin	Long term effects	Company data

PNEC	Exposure route	Source
199,5 mg/l	Waste water treatment	Company data
0,0072 mg/kg	marine water	Company data
0,017 mg/l	freshwater	Company data

2,2'-[(4-methylphenyl)imino]bisethanol

*DNEL	Target group	Exposure route	Exposure frequency	Source
0,47 mg/kg	Workers	dermal exposure	Long term effects	Company data
			systemic	

*PNEC	Exposure route	Source
0,003 mg/l	seawater	Company data
0,121 mg/kg	freshwater sediment	Company data
0,026 mg/l	freshwater	Company data
0,012 mg/kg	marine sediment	Company data
10 mg/l	Waste water treatment	Company data
0,009 mg/kg	soil	Company data

8.2 Exposure controls

Respiratory protection	In interiors and during exceeding of the air limit values carrying of protective masks is absolutely necessary. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Remarks	Recommended Filter type: A1, A2 (in case of higher concentration)
Hand protection	Protective gloves complying with EN 374.Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Unsuitable material	woven fabric, Leather gloves
Suitable material	Nitrile
Eye protection	Tightly fitting safety goggles
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and at the end of workday. Use protective skin cream be-fore handling the product. Avoid contact with the skin and the eyes.
Engineering measures	Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	flüssig
Form	liquid
Colour	different color-tone
Odour	smell of Methylmethacrylate
рН	not applicable
Boiling point [°C]	>100 °C
Flash point [°C]	10 °C
Evaporation rate [kg/(s m ²)]	not determined

Replaces version from: 21.09.2018 Print date: 11.03.2022

Explosion limits [Vol-%]	The product itself has not been tested. methyl methacrylate
Lower limit	1,7 vol. %
Upper limit	12,5 vol. % 2-ethylhexyl acrylate
Lower limit	0,9 vol. %
Upper limit	6,4 vol. %
Vapour pressure [kPa]	not determined
Vapour density	not determined
Density [g/cm ³]	1,33 g/cm³
Water solubility [g/l]	
Remarks	insoluble
Partition coefficient n-octanol /water (log P O/W)	not determined
Autoignition temperature [°C]	not determined
Viscosity, dynamic [kg/(m s)]	1.500 mPa.s
Measuring method	Haake-Viscotester
Explosive properties	Not relevant In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	Not relevant
9.2 Other information	
Ignition temperature [°C]	280 °C

SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions	The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution. Risk of receptacle bursting.		
10.4 Conditions to avoid	1		
Conditions to avoid	Extremes of temperature and direct sunlight.		
10.5 Incompatible mater	10.5 Incompatible materials		
Materials to avoid	Reacts violently with peroxides. Reducing agents, Strong bases, Amines, Oxidizing agents		

SECTION 11: Toxicological information

11.1 Information on toxicological effects

*Oral toxicity [mg/kg]

Hazardous ingredients

methyl methacrylate				
Value	Test criterion	Test species	Measuring method	Source
>5001 mg/kg	LD50	rat	OECD Test Guideline 401	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
4435 mg/kg	LD50	rat	Company data

aliphatic urethanacry	ate		
Value	Test criterion	Test species	Source
>2001 mg/kg	LD50	rat	Company data

1,1`-(p-Tolylimi	no)dipropan-2-ol			
Value	Test criterion	Test species	Measuring method	Source
26 mg/kg	LD50	rat	OECD Test Guideline 423	Company data

*2,2'-[(4-methylphenyl)imino]bisethanol		
Value	Test criterion	Test species	Source
959 mg/kg	LD50	rat	Company data

*Dermal toxicity [mg/kg]

Hazardous ingredients			
methyl methacrylate			
Value	Test criterion	Test species	Source
>5001 mg/kg	LD50	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
7522 mg/kg	LD50	rabbit	Company data

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Source	
2001 mg/kg	LD50	rat	Company data	
*2,2'-[(4-methylphenyl)imino]bisethanol			
Value	Test species	Measuring method	Source	

Commercial Product Name: Bauder LiquiBALKON WI 10 k Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en BAUDER

e toxicity [mg/l] dous ingredients -ethylhexyl acrylate /alue _19 mg/l lation 4h for vapours [mg/l] dous ingredients nethyl methacrylate /alue Tes 9,8 mg/l LC5	Test species rat t criterion	402	Source Company data
dous ingredients e-ethylhexyl acrylate /alue ,19 mg/l lation 4h for vapours [mg/l] dous ingredients nethyl methacrylate /alue Tes 9,8 mg/l LC5	rat t criterion		Company data
/alue ,19 mg/l lation 4h for vapours [mg/l] dous ingredients nethyl methacrylate /alue Tes 9,8 mg/l LC5	rat t criterion		Company data
,19 mg/l lation 4h for vapours [mg/l] dous ingredients nethyl methacrylate /alue Tes 9,8 mg/l LC5	rat t criterion		Company data
lation 4h for vapours [mg/l] dous ingredients nethyl methacrylate /alue Tes 9,8 mg/l LC5	t criterion		Source
nethyl methacrylate /alue Tes 9,8 mg/l LC5			
9,8 mg/l LC5			
I	0	rat	Compony date
fect on skin			Company data
ritating	rabbit		Company data
-ethylhexyl acrylate			
	t species	Exposure duratio [h]	
Skin irritation rabl	DIT	4 h	Company data
liphatic urethanacrylate		0	
Value May cause skin irritation.		Source Company data	
		Company data	
,1`-(p-Tolylimino)dipropan-2-o	bl		
/alue		Source	
lo skin irritation		Company data	
,2'-[(4-methylphenyl)imino]bis	sethanol		
/alue	Test species		Source

Commercial Product Name: Bauder LiquiBALKON WI 10 k Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en BAUDER

slightly irritating	OECD Test Guideline 405	rabbit	Company data
aliphatic urethanacry	late		
Value		Source	
Causes serious eye irritat	ion.	Company data	
1,1`-(p-Tolylimino)dip	ronan 2 al		
Value	ropan-z-or	Source	
Irritant		Company data	
intant		Company data	
2,2'-[(4-methylphenyl)	imino]bisethanol		
Value		Source	
Risk of serious damage to	eyes.	Company data	
ardous ingredients methyl methacrylate Value	Test species		Source
Skin sensitization	mouse		Company data
Skin sensitization 1,1`-(p-Tolylimino)dip Value No sensitization response *2,2'-[(4-methylpheny Value No known effect.	es were observed.	Company data Source Company data Source Company data	
genic effects ardous ingredients methyl methacrylate Value not a carcinogen	Test species rat, mouse		Source Company data
	I		
2-ethylhexyl acrylate			
Value		Source	
No known effect.		Company data	

Commercial Product Name: Bauder LiquiBALKON WI 10 Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en BAUDE

Value	Source
not mutagenic	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
negative	Company data

2,2'-[(4-methylphenyl)imino]bisethanol					
Value	Measuring method	Test species	Remarks	Source	
negative	Ames test	Bacteria	In vitro methods	Company data	

*Reproduction toxicity

Hazardous ingredients	
methyl methacrylate	
Value	Source
not toxic to reproduction	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

Specific target organ toxicity (single exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate			
Value	Source		
Causes respiratory tract irritation.	Company data		

2-ethylhexyl acrylate	
Value	Source
Causes respiratory tract irritation.	Company data

*Specific target organ toxicity (repeated exposure) [mg/kg]

methyl methacrylate	
Value	Source
No known effect.	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes, respiratory system and skin. Irritatingto mucous membranes

SECTION 12: Ecological information

12.1 Toxicity

*Toxicity to fish [mg/l]

Hazardous ingredients

methyl meth	methyl methacrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source		
191 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data		

2-ethylhexyl	2-ethylhexyl acrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source		
1,81 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data		

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure dura- tion [h]	Source	
17 mg/l	LC50	Brachydanio rerio (zebra fish)	96 h	Company data	

*2,2'-[(4-methylphenyl)imino]bisethanol						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source	
101 mg/l	LC50	Brachydanio rerio (zebra fish)	OECD Test Guideline203	96 h	Company data	

*Toxicity to daphnia [mg/l]

methyl methacrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
69 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

Commercial Product Name: Bauder LiquiBALKON WI 10 k Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

BAUDER

2-ethylhexyl acrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
1,3 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

aliphatic urethanacrylate					
Value	Test criterion	Test species	Source		
>100 mg/l	LC50	Daphnia magna (Water flea)	Company data		

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure duration [h]	Source	
28,8 mg/l	EC50	Daphnia magna (Water flea)	18 h	Company data	

*2,2'-[(4-methylphenyl)imino]bisethanol						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
48 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

*Toxicity to algae [mg/l]

Hazardous ingredients

methyl meth	methyl methacrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
>110 mg/l	EC50	Selenastrum capricornu- tum (green algae)	72 h	OECD Test Guideline201	Company data		

2-ethylhexyl acrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
1,71 mg/l	ErC50	Desmod- esmus sub- spicatus	72 h	OECD Test Guideline201	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure dura- tion [h]	Source	
245 mg/l	EC50	Desmodesmus subspicatus	27 h	Company data	

*2,2'-[(4-methylphenyl)imino]bisethanol

Commercial Product Name: Bauder LiquiBALKON WI 10 kg Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 11.03.2022

BAUDER

Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
>101 mg/l	ErC50	Pseudokirch- neriella sub- capitata	72 h	OECD Test Guideline201	Company data

NOEC (fish) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
9,4 mg/l	Brachydanio rerio (ze- bra fish)	OECD Test Guideline 210	Company data

NOEC (daphnia) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
37 mg/l	Daphnia magna (Water flea)	OECD Test Guideline 202	Company data

NOEC (algae) [mg/l]

Hazardous ingredients

2-ethylhexyl acrylate			
Value	Test species	Measuring method	Source
0,45 mg/l	Desmodesmus subspi- catus	OECD Test Guideline 201	Company data

12.2 Persistence and degradability

*Biodegradability

methyl methacrylate		
Value	Method of analysis	Source
Readily biodegradable.	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	Company data

2-ethylhexyl acrylate	
Value	Source
Readily biodegradable.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Poorly biodegradable.	Company data

2,2'-[(4-methylphenyl)imino]bisethanol	
Value	Source
Not readily biodegradable.	Company data

12.3 Bioaccumulative potential

*Bioaccumulation

Hazardous ingredients

methyl methacrylate	
Value	Source
Does not bioaccumulate.	Company data

2-ethylhexyl acrylate	
Value	Source
Bioaccumulation slight, log Pow 4,64	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
no data available	Company data

12.4 Mobility in soil

Mobility

Hazardous ingredients

methyl methacrylate	
Mobility	Source
Terrestrial Compartment Not relevant	Company data

12.5 Results of PBT and vPvB assessment

*Results of PBT characteristics determination

methyl methacrylate	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

2-ethylhexyl acrylate	
Value	Source
This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

aliphatic urethanacrylate		
Value	Source	
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Bauder LiquiBALKON WI 10 kg Article-No.: GB81002405 Revision Date: 11.03.2022 Version: 2.0/en

Replaces version from: 21.09.2018 Print date: 11.03.2022

This substance is not considered to be persistent, Con bioaccumulating nor toxic (PBT).	ompany data
---	-------------

2,2'-[(4-methylphenyl)imino]bisethanol	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

12.6 Other adverse effects

Further information on ecology

We have no quantitative data concerning the ecological effects of this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The following Waste Codes are only suggestions:
Waste Code	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Uncleaned empty packaging	Empty containers should be taken for local recycling or waste disposal. Dispose of in accordance with local regulations.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.2 Description of the	PAINT	FARBE	Farbe
goods			
UN proper shipping name		PAINT	Paint
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group	111	111	
Labels	3	3	3 - Flammable Liquid
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
SP 640	640E		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		A	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC Code Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations	Additionally, observe any national regulations!
Classification in compliance withthe Industrial Safety Regulation	highly flammable
GISCODE	RMA10
MAL-Code	4-5

SECTION 16: Other information

	Modifications since last version	Modifications of the previous version are denoted with an asterisk (*).		
	Relevant H-phrases	H225: Highly flammable liquid and vap H300: Fatal if swallowed. H302: Harmful if swallowed.	our.	
		H315: Causes skin irritation.		
		H317: May cause an allergic skin reaction.		
		H318: Causes serious eye damage.		
		H319: Causes serious eye irritation.		
		H335: May cause respiratory irritation. H412: Harmful to aquatic life with long lasting effects.		
	Wording of the hazard classes			
	Wording of the hazard classes	Flam. Liq.: Flammable liquid STOT SE: Specific target organ toxicity -	•	
		Skin Irrit.: Skin irritation		
		kin Sens.: Skin sensitization		
		Aquatic Chronic: Hazardous to the aquatic environment		
		Eye Irrit.: Serious eye irritation		
		Acute Tox.: Acute toxicity		
		Eye Dam.: Serious eye damage		
,	 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP] 	Classification	Evaluation	
		Flam. Liq. 2; H225	Calculated	
		Skin Irrit. 2; H315	Calculated	
		Skin Sens. 1; H317	Calculated	
		STOT SE 3; H335	Calculated	
	Recommended restrictions	Reserved for industrial and professional use.		

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.