Declaration of Performance BauderBIT G 200 DD DoP-No.: 0801 0000



1.	Unique identification code of the product-type	BauderBIT G 200 DD - 1_01		
2.	Intended use/es	Reinforced bitumen sheets for roof waterproofing	Bitumen damp proof sheets including bitumen basement tanking sheets	Bitumen damp proof courses
3.	Manufacturer	Paul Bauder GmbH & Co. KG, Korntaler Landstrasse 63, 70499 Stuttgart, Germany		
4.	System/s of assessment and verification of constancy of performance of the construction product	System 2+	System 2+	System 3
5.	Harmonised standard Notified body	EN 13707:2004 + A2:2009	EN 13969:2004 + A1:2006	EN 14967:2006

6. Declared performance

Essential characteristics	Performance EN 13707:2004 + A2:2009	Performance EN 13969:2004 + A1:2006	Performance EN 14967:2006
External fire performance ^{a)}	NPD		
Reaction to fire	E	Е	E
Watertightness	passed	passed	passed
Tensile properties: Max. tensile force length Max. tensile force transverse Elongation at max. tensile force length Elongation at max. tensile force transverse (%)	≥1000 ≥1000 ≥2 ≥2	≥1000 ≥1000 ≥2 ≥2	
Resistance to root penetration	NPD		
Resistance to static loading (kg)	NPD	NPD	
Resistance to impact (mm)	NPD	NPD	NPD
Tear resistance length (N) Tear resistance transversal (N)	NPD NPD	NPD NPD	
Joint strength: Peel resistance (N/50mm) Shear resistance (N/50mm)	NPD NPD	NPD NPD	
Durability: Watertightness after artificial ageing Watertightness after exposure to chemicals after artificial ageing		NPD NPD	NPD NPD
Flexibility at low temperature top (°C) Flexibility at low temperature bottom (°C)	≤0 ≤0	≤0 ≤0	≤0 ≤0
Hazardous substances ^{b),c)}	Passed,see 5.3 EN 13707:2004 + A2:2009	Passed,see 5.15 EN 13969:2004 + A1:2006	Passed,see 5.14 EN 14967:2006

Declaration of Performance BauderBIT G 200 DD DoP-No.: 0801 0000



- a) Determination of external fire performance is a system test which can be influenced by system components, which are not produced or sold by Bauder GmbH, thus performance for each product can not be given.
- b) Product does not contain asbestos or tar
- c) Because there is no European test method for leaching of the products, no statement can be made.

NPD = no performance declared

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mark Bauder, Managing Director

Mark Bancles

Stuttgart, 28.11.2022