

Technical data sheet


BauderPVC DP 25

Decor profile



V3 22/11/2022

Product description	Bauder Décor PVC profile simulates the visuals of a standing seam metal profile.
Application fields	Suitable with all BauderTHERMOFOL membranes.
Colour	blue grey RAL 7031
Article number	6025 6000



Characteristic	Unit	Value
Visible defects	-	no visible defects
Length	m	3,0
Width	mm	35
Height	mm	25
Processing	-	Hot air welding with approx. 470 °C
Material	-	PVC-P
Overall thickness	mm	2,0
External fire performance	-	not applicable

Installation guidance	Décor profile is heat welded onto the PVC membrane at 470°C with a hot air welding gun. Before installation begins, clean the membrane with Bauder PVC cleaner and mark the profile centre spacing on the field sheet membrane with a chalk line.
Handling/PPE	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using/handling the product, installers should be provided with, and wear, suitable personal protective equipment.
Further information/documents	Current documents such as DoC's, DoP's (where relevant), brochures, installation guides, etc. can be found by visiting www.bauder.co.uk
Safety Data Sheet	Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.