


## Bauder Thermotech Glass Insulation

18.05.2026

<b>Product description</b>	PIR insulation board with a coated glass tissue facing on both sides, available in a uniform thickness or tapered to falls.
<b>Application fields</b>	This product is designed for use with torch-applied, self-adhesive or adhered waterproofing membranes.
<b>Facing</b>	top: Coated glass tissue bottom: Coated glass tissue
<b>Board edge</b>	Square (not rebated)
<b>Board size</b>	Flatboard 25 to 150mm Tapered varies
<b>Website Link</b>	<a href="https://www.bauder.co.uk/products/thermotech-glass-insulation">https://www.bauder.co.uk/products/thermotech-glass-insulation</a>



Characteristic	Test method	Unit	Value
<b>External dimension</b>	EN 822	mm	Flatboard 1200 length x 600 width Tapered 1200 length x 1200 width
<b>Thickness</b>	EN 823	mm	Flatboard = 25 to 150 Tapered varies
<b>Weight</b>		Kg/m <sup>3</sup>	32
<b>Reaction to fire</b>	EN 13501 - 1	-	F
<b>Compressive strength (with 10% compression)</b>	EN 826	kPa	≥150
		N/mm <sup>2</sup>	0.15
<b>Thermal conductivity (λ<sub>D</sub>) - (EU)</b>	EN 13165	Kg/m <sup>2</sup>	15,000
		W/mK	Up to 80mm = 0.027
		W/mK	80 to 119mm = 0.025 120 to 150mm = 0.024
<b>Tapered falls available</b>			1:60 & 1:80
Compressive strength for permanently sited loads – please contact Bauder Ltd where plant/equipment is to be sited on top of the Bauder system			

<b>Normative references</b>	For updated references, the latest edition of the referenced document (including any amendments) applies.
<b>Storage/ Transport</b>	Store the materials outdoors with suitable robust UV resistant, flame-retardant tarpaulin. Ensure the product(s) are clear of buildings and any other storage areas. The products must not be exposed to a direct naked flame or other ignition sources, or to solvents or other chemicals. All insulation boards must be kept dry, on pallets and off the ground. The packaging of Bauder Insulation products should not be considered adequate for weather protection. Where there are storage containers on site, these may be suitable for storing products.
<b>Product storage guidance</b>	All insulation boards must be kept dry, on pallets and off the ground. The packaging of Bauder Insulation products should not be considered adequate for outside protection. Ideally boards should be stored inside a building. If outside storage cannot be avoided the boards should be stacked clear of the ground and covered with an opaque polythene sheet or weatherproof tarpaulin.
<b>Packaging material</b>	The product will be delivered on EPS skids or wooden pallets with polythene overwrap to protect the product.
<b>Handling/PPE</b>	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.
<b>Shelf life</b>	When stored correctly, the product has no stated shelf life.
<b>Disposal guidance</b>	Rigid polyurethane foam waste can be disposed of with household waste or commercial waste similar to household waste (European waste catalogue EWC number 170604 "Insulation material").
<b>Re-use options of product</b>	Please refer to EPD stated below in Certification and environmental information.
<b>Further information/ documents</b>	Current documents such as brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>
<b>Certification and environmental information</b>	<b>BBA Certificate No:</b> 16/5332

# Technical data sheet



**Environmental Product Declaration:** EPD-IVP-20210002-IBE1-EN

**International Standards Organisation (ISO)**

**ISO 9001:2015 Quality Management**  
Certificates EN1271 (UK) and 70499/03-15\_e (Germany)

**ISO 14001:2015 Environmental Management Certificates**  
A10552 (UK) and 70499/03-15\_d (Germany)

**Installation Guidance:** Please refer to the Bauder Installation Guide and project specification for guidance.

- Insulation must be installed in dry conditions
- The product is easily trimmed and shaped, therefore if the substrate or abutment is uneven, it's easy to modify the insulation by cutting to fit.
- Tapered insulation must be installed in accordance with the project specific tapered scheme design.

**Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.**



DoP can be found via the website



DoC can be found via the website