

Declaration of Performance

DoP-Nr.: 1601 0000

1.	Unique identification code of the product-type	BauderTEC KSD Alu-Folie/Abziehfolie
2.	Intended use/es	Bitumen water vapour control layers
3.	Manufacturer	Paul Bauder GmbH & Co. KG, Korntaler Landstrasse 63, 70499 Stuttgart, Germany
4.	System/s of assessment and verification of constancy of performance of the construction product	System 3
5.	Harmonised standard Notified body	EN 13970: 2005 + A1: 2007 Notified testing laboratory No. 0672 (MPA Stuttgart) determined the production type under system AVCP 3.

6. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 13501-1: 2010
Water tightness, method B	passed	EN 13970:2005 + A1: 2007
Tensile properties:		
Max. Tensile force length (N/50 mm)	≥ 400	
Max. Tensile force transverse (N/50 mm)	≥ 300	
Elongation at max. tensile force length (%)	≥ 2	
Elongation at max. tensile force transverse (%)	≥ 2	
Flexibility at low temperature (°C)	≤ -30	
Water vapour transmission (m)	≥ 1500	
Hazardous Substances ^{b), c)}	Passed, see 5.14 EN 13970	

For all other characteristics according to EN 13970: NPD (no performance determined)

- b) Product does not contain asbestos or tar
c) Because there is no European test method for leaching of the products, no statement can be made

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Gerhard Bauder
Managing Director
Stuttgart, 23.01.2017