


PRODUCT DATA SHEET

Bauder Thermoplan T SV 15 Fleece-Backed Membrane

Bauder Thermoplan T SV 15 Fleece-Backed Membrane is a polyester reinforced flexible polyolefin membrane (FPO), an alloy of thermoplastic and rubber. A polyester fleece is laminated to the underside of the membrane in factory conditions. This combination gives high tensile strength, good thermal stability, chemical resistance and flexibility.



PRODUCT INFORMATION AND TECHNICAL PERFORMANCE		
Weights and Sizes	Unit	Value
Roll width	m	1.5
Roll length	m	20
Thickness	mm	2.5mm (1.5 membrane + 1 fleece)
Weight	kg/m ²	2.1
Reinforcement		Pre-coated cross-weave polyester (synthetic PES fibre fabric and bottom side fleece laminated)

SURFACE FINISHES	MEMBRANE COLOURS
Top:	Pearl White – RAL 1013 
Bottom:	Polyester fleece

UNITED KINGDOM

Bauder Ltd
70 Landseer Road, Ipswich, Suffolk IP3 0DH
T: +44 (0)1473 257671 E: info@bauder.co.uk
bauder.co.uk

IRELAND

Bauder Ltd
O'Duffy Centre, Carrickmacross, Co. Monaghan
T: +353 (0)42 9692 333 E: info@bauder.ie
bauder.ie

PRODUCT DATA SHEET

PRODUCT INFORMATION AND TECHNICAL PERFORMANCE			
Characteristics	Test method	Unit	Value
External fire performance*	EN 13501-5		No performance declared
Reaction to fire	EN 13501-1		Class E according to EN 13501-1
Watertightness method B			Passed
Tensile force	md	N/mm	≥ 1200/50
	cd	N/mm	≥ 1200/50
Elongation at maximum tensile force	md	%	≥ 19
	cd	%	≥ 19
Root Resistance			FLL Passed
Resistance to impact	Hard surface	mm	>800
	Soft surface	mm	>1250
Resistance to static loading	Hard surface	kg	≥ 20
	Soft surface	kg	≥ 20
Tear resistance		N	> 550
Joint peel resistance		N	≥ 300
Joint shear resistance		N	≥ 500
Durability		h	Passed
Foldability		°C	≤ -30
Dangerous substances			No performance declared

* Determination of external fire performance is a system test, which can be influenced by system components, which are not produced or sold by Bauder Limited, thus performance for each product cannot be given.

CERTIFICATION AND ENVIRONMENTAL INFORMATION	
BBA Certificate	BBA Fire Rating – Test results indicate the product to be designated as being Un-Restricted 04/4120
Environmental Product Declaration (EPD)	EPD-BAU-20130189-IBCC-DE
International Standards Organisation (ISO)	ISO 9001:2015 Quality Management Certificates EN1271 (UK) and 70499/03-15_e (Germany). ISO 14001:2015 Environmental Management Certificates A10552 (UK) and 70499/03-15_d (Germany). ISO 50001: 2011 Energy Management Certificate 70499/03-15_c
BRE Green Guide generic product rating	A+

INSTALLATION GUIDANCE
Refer to the FPO Laying Instructions Bauder Thermoplan Guide.

UNITED KINGDOM

Bauder Ltd
 70 Landseer Road, Ipswich, Suffolk IP3 0DH
 T: +44 (0)1473 257671 E: info@bauder.co.uk
bauder.co.uk

IRELAND

Bauder Ltd
 O'Duffy Centre, Carrickmacross, Co. Monaghan
 T: +353 (0)42 9692 333 E: info@bauder.ie
bauder.ie