Declaration of Performance BauderFLEX TA 600 DoP-No.: 1794 0000



| 1. | Unique identification code of the product-type | BauderFLEX TA 600 - 1_01 |
|----|---|---|
| 2. | Intended use/es | Reinforced bitumen sheets for roof waterproofing |
| 3. | Manufacturer | Paul Bauder GmbH & Co. KG, Korntaler Landstrasse 63, 70499 Stuttgart, Germany |
| 4. | System/s of assessment and verification of constancy of performance of the construction product | System 2+ |
| 5. | Harmonised standard Notified body | EN 13707:2004 + A2:2009 GPB, 1724 |

6. Declared performance

| Essential characteristics | Performance EN 13707:2004 + A2:2009 |
|--|--|
| External fire performance ^{a)} | NPD |
| Reaction to fire | E |
| Watertightness | passed |
| Tensile properties: Max. tensile force length Max. tensile force transverse Elongation at max. tensile force length Elongation at max. tensile force transverse (%) | ≥550 ≥300 ≥20 ≥20 |
| Resistance to root penetration | NPD |
| Resistance to static loading (kg) | NPD |
| Resistance to impact (mm) | NPD |
| Tear resistance length (N) Tear resistance transversal (N) | ≥130 ≥130 |
| Joint strength: Peel resistance (N/50mm) Shear resistance (N/50mm) | NPD NPD |
| Durability: Flexibility at low temperature after artificial ageing top (°C) | NPD |
| Flexibility at low temperature after artificial ageing bottom (°C) | NPD |
| Flexibility at low temperature top (°C) Flexibility at low temperature bottom (°C) | ≤-20 ≤-20 |
| Hazardous substances ^{b),c)} | Passed,see 5.3 EN 13707:2004 + A2:2009 |

Declaration of Performance BauderFLEX TA 600 DoP-No.: 1794 0000



- a) Determination of external fire performance is a system test which can be influenced by system components, which are not produced or sold by Bauder GmbH, thus performance for each product can not be given.
- b) Product does not contain asbestos or tar
- c) Because there is no European test method for leaching of the products, no statement can be made.

NPD = no performance declared

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mark Bauder, Managing Director

Mark Bancles

Stuttgart, 28.11.2022