

PRODUCT DATA SHEET

Bauder GRP Trim Angle

A high quality, maintenance free, GRP roof edge trim for use with Bauder LiquiTEC roof and balcony systems. It has a far lower coefficient of thermal expansion than aluminium or steel, along with a higher strength to weight ratio.

**Intended Use**

Bauder GRP Trim Angle is used where the LiquiTEC system is terminated at perimeter details, such as drip edges, watercheck kerbs or parapets.

PRODUCT DATA

Length	3m
Face depth*	60mm
Fixing arm*	100mm
Thickness	2mm
Colour	Black
Pack size	10

INSTALLATION GUIDANCE

*Bauder GRP Trim Angle may be used in either orientation depending on the situation.

The trims must be bedded in LiquiPASTE and mechanically fixed with corrosion resistant flush headed screws. Fixings centres must be no greater than 300mm with fixings within 50mm of the ends. In high wind risk areas or above 10m high, fixing centres are to be at no more than 150mm.

The reinforced LiquiDETAIL system is to be dressed over the trim to its full extent and past the edge of the downward facing edge. Once the system has cured, the excess is to be trimmed off to a neat finish.

Bauder reserves the right to amend information and product specifications without prior notice. All reasonable care has been taken to ensure that all data is current at the time of print, however because Bauder pursues a policy of constant development we recommend ensuring that your copy of this information is current by contacting our Technical Department at technical@bauder.co.uk

Recommendations for use should be verified as to the suitability and compliance with actual requirements, specifications, installation techniques and any applicable laws and regulations.

UNITED KINGDOM

Bauder Ltd

70 Landseer Road, Ipswich, Suffolk IP3 0DH

T: +44 (0)1473 257671 E: info@bauder.co.ukbauder.co.uk**IRELAND**

Bauder Ltd

O'Duffy Centre, Carrickmacross, Co. Monaghan

T: +353 (0)42 9692 333 E: info@bauder.iebauder.ie