

## TECHNICAL DATA SHEET

### Bauder X4S Capping Sheet

#### DESCRIPTION

High performance, torch-applied elastomeric bitumen capping sheet for use in areas that will not be exposed to ultraviolet light. The product features a spunbond polyester reinforcement to allow the finished product to cope with structural movement without fracture. This product is generally used beneath paving slabs or promenade tiles.

#### TECHNICAL DATA:

##### Weights and sizes

Roll width:	1 metre
Roll length:	10 metres
Thickness:	4.2 mm
Weight:	5 Kg/m <sup>2</sup>
Reinforcement:	250 g/m <sup>2</sup> spunbond polyester

##### Surface finishes

Top:	mica
Bottom:	thermofusible polyethylene

##### Technical performance

Tensile strength:	length	≥ 800N/50mm
	diagonal	≥ 800N/50mm
Elasticity at fracture of re-inforcement:	length	≥ 35%
	diagonal	≥ 35%
Cold bending test:	-25°C	
Softening point:	+100°C	



#### UNITED KINGDOM

##### Bauder Ltd

70 Landseer Road  
Ipswich Suffolk England IP3 0DH  
**T:** +44 (0)1473 257671 **E:** info@bauder.co.uk  
[bauder.co.uk](http://bauder.co.uk)

#### IRELAND

##### Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross  
Co. Monaghan Ireland  
**T:** +353 (0)42 9692 333 **E:** info@bauder.ie  
[bauder.ie](http://bauder.ie)