

## PRODUCT DATA SHEET

### Bauder BioSOLAR




Bauder BioSOLAR is an integrated solar PV mounting system specifically for Bauder biodiverse or extensive green roofs.

#### Intended Use

Bauder BioSOLAR is designed for applications where both a green roof and solar PV solution are required to meet planning and/or BREEAM requirements. The green roof substrate and vegetation provide the ballast mechanism for the entire solution which removes the need for penetrating the waterproofing to secure the units to the roof and maximises the available area for vegetation establishment.

Bauder BioSOLAR should be used in conjunction with our Bauder Flora 3 Seed Mix which contains both drought and shade tolerant herb and wildflower species and is suitable for roofs with a fall of up to 3°.



No.	Sketch	Name	Description
1		Anchor Board 2m x 1m	<b>Profiled Substructure</b> for containing substrate and mounting BioSolar angle bracket.
2		Quick fix Angle Bracket 164cm x 5cm x 5cm	<b>Aluminium Angle Bracket</b> for mounting module rail.
3		Module Carrier Rail 6m x 4.5cm x 4.5cm	<b>Aluminium Profiled Rail</b> for mounting framed modules.







#### UNITED KINGDOM

Bauder Ltd  
70 Landseer Road, Ipswich, Suffolk IP3 0DH  
T: +44 (0)1473 257671 E: [info@bauder.co.uk](mailto:info@bauder.co.uk)  
[bauder.co.uk](http://bauder.co.uk)

#### IRELAND

Bauder Ltd  
O'Duffy Centre, Carrickmacross, Co. Monaghan  
T: +353 (0)42 9692 333 E: [info@bauder.ie](mailto:info@bauder.ie)  
[bauder.ie](http://bauder.ie)

## PRODUCT DATA SHEET

No.	Sketch	Name	Description
		Screw M8 x 55 A2	<b>55mm Fixing Screw</b> for Quick-Fix angle bracket. 6mm Hex bit required.
		Screw M8 x 20 A2	<b>20mm Fixing Screw</b> for module rail to angle bracket. TX40 bit required.
		Middle Clamp	<b>Clamp</b> for fixing modules within the row.
		End Clamp	<b>Clamp</b> for fixing modules at the end of the row.
		Sealing Cap	<b>Plastic Cap</b> to protect cut ends of the module carrier rail.
		Profile Connector	<b>Aluminium Profile</b> to connect lengths of module rail over 6m in length.

### PRODUCT INFORMATION AND TECHNICAL PERFORMANCE

Characteristic	Test method	Unit	Value
Weight	EN 1848-1	kg/m <sup>2</sup>	156*

\* Includes weight of solar module & saturated Biodiverse green roof based on substrate depth of 130mm

### CERTIFICATION AND ENVIRONMENTAL INFORMATION

International Standards Organisation (ISO)	<p>ISO 9001:2015 Quality Management Certificates EN1271 (UK) and 70499/03-15_e (Germany).</p> <p>ISO 14001:2015 Environmental Management Certificates A10552 (UK) and 70499/03-15_d (Germany).</p> <p>ISO 50001: 2011 Energy Management Certificate 70499/03-15_c (Germany)</p>
--	---

#### UNITED KINGDOM

Bauder Ltd  
70 Landseer Road, Ipswich, Suffolk IP3 0DH  
T: +44 (0)1473 257671 E: [info@bauder.co.uk](mailto:info@bauder.co.uk)  
[bauder.co.uk](http://bauder.co.uk)

#### IRELAND

Bauder Ltd  
O'Duffy Centre, Carrickmacross, Co. Monaghan  
T: +353 (0)42 9692 333 E: [info@bauder.ie](mailto:info@bauder.ie)  
[bauder.ie](http://bauder.ie)

## PRODUCT DATA SHEET

**INSTALLATION GUIDANCE**

Bauder Biosolar is designed to be installed by a Bauder approved and trained contractor only. Please see Bauder Biosolar installation guidelines for a full breakdown of the system installation methodology.

The number of mounts and fixings required will vary from project to project. Please contact Bauder for a project specific technical report for further information. Windload and snowload calculations will also be provided on a project specific basis and will determine ballast requirements and substrate depths.

Bauder Biosolar can be installed on slopes of up to 3° and is intended to be used with Bauder Biodiverse and substrate based extensive green roofs only.

Bauder reserves the right to amend information and product specifications without prior notice. All reasonable care has been taken to ensure that all data is current at the time of print, however because Bauder pursues a policy of constant development we recommend ensuring that your copy of this information is current by contacting our Technical Department at [technical@bauder.co.uk](mailto:technical@bauder.co.uk).

Recommendations for use should be verified as to the suitability and compliance with actual requirements, specifications, installation techniques and any applicable laws and regulations.

**UNITED KINGDOM**

Bauder Ltd

70 Landseer Road, Ipswich, Suffolk IP3 0DH

T: +44 (0)1473 257671 E: [info@bauder.co.uk](mailto:info@bauder.co.uk)[bauder.co.uk](http://bauder.co.uk)**IRELAND**

Bauder Ltd

O'Duffy Centre, Carrickmacross, Co. Monaghan

T: +353 (0)42 9692 333 E: [info@bauder.ie](mailto:info@bauder.ie)[bauder.ie](http://bauder.ie)