

## TECHNICAL DATA SHEET

### Bauder LiquiTEC System

#### LiquiFINISH

##### DESCRIPTION

LiquiFINISH is a cold liquid applied fast curing final coat, used to seal and bind the quartz wearing course in LiquiTEC Balcony, Walkway & Terrace Systems, and also to provide the desired colour to the finished waterproofing. It can also be used to provide a colour change to the LiquiTEC Roof system, or as a carrier for anti-skid granules when specified. The product is a PMMA based resin and requires the addition of catalyst to trigger curing. It is solvent, isocyanate and halogen free, minimizing its environmental impact.

##### TECHNICAL DATA:

Standard Colours:	Blue grey (Approx.RAL 7031), Traffic grey (Approx.RAL 7043), Stone grey (Approx.RAL 7030)
Coverage:	Approx. 0.65Kg/m <sup>2</sup> over quartz, 0.50Kg/m <sup>2</sup> to smooth areas.
Pack size:	10Kg re-sealable drum
Application temperature:	0°C to 35°C
Rainproof time:	30 minutes approx.
Traffic time:	1 hour approx.

##### UNITED KINGDOM

###### Bauder Ltd

70 Landseer Road

Ipswich Suffolk England IP3 0DH

**T:** +44 (0)1473 257671 **E:** info@bauder.co.uk

**bauder.co.uk**

##### IRELAND

###### Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross

Co. Monaghan Ireland

**T:** +353 (0)42 9692 333 **E:** info@bauder.ie

**bauder.ie**