

TECHNICAL DATA SHEET

Bauder LiquiTEC System

LiquiPAVE R

DESCRIPTION

LiquiPAVE R is an unpigmented cold liquid applied fast curing waterproofing resin used in conjunction with 110g Reinforcement Fleece for overbanding of dynamic cracks and joints in the substrate prior to installing the Deck Floor Layer.

It is also the resin component of LiquiPAVE RF Deck Floor Layer.

LiquiPAVE R is a PMMA based resin and requires the addition of catalyst to trigger curing. It is solvent, isocyanate and halogen free, minimizing its environmental impact.

TECHNICAL DATA:

Coverage:	Depends on application (refer to specification)
Pack size:	10Kg re-sealable drum
Application temperature:	0°C to 35°C
Rainproof time:	30 minutes approx.
Traffic / overcoat time:	1 hour approx. (for overbanding).

UNITED KINGDOM

Bauder Ltd

70 Landseer Road

Ipswich Suffolk England IP3 0DH

T: +44 (0)1473 257671 **E:** info@bauder.co.uk

bauder.co.uk

IRELAND

Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross

Co. Monaghan Ireland

T: +353 (0)42 9692 333 **E:** info@bauder.ie

bauder.ie