

TECHNICAL DATA SHEET

BauderTEC KSA DUO Underlayer

DESCRIPTION

A technically advanced self-adhesive elastomeric bitumen underlayer with "DUO" lap technology to ensure thorough sealing of lap joints, even in lower temperatures. The product features a glass lattice reinforcement for strength and stability.

The product benefits from cleaner, safer and faster installation than traditional torch applied membranes.

TECHNICAL DATA:

Weights and sizes

Roll width	1 metre
Roll length	7.5 metres
Thickness:	3mm
Weight:	3.5Kg/m ²
Reinforcement:	200g/m ² glass lattice

Surface finishes

Top:	foil
Bottom:	peel off release film covering self-adhesive bitumen

Technical performance

Tensile strength:	length	≥ 1000N/50mm
	diagonal	≥ 1000N/50mm
Elasticity at fracture of reinforcement:	length	≥ 2%
	diagonal	≥ 2%
Cold bending test:	top	-25°
	bottom	-30°C
Softening point:		+100°C

Shelf life 9 months from date of manufacture



UNITED KINGDOM

Bauder Ltd

70 Landseer Road
Ipswich Suffolk England IP3 0DH
T: +44 (0)1473 257671 **E:** info@bauder.co.uk
bauder.co.uk

IRELAND

Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross
Co. Monaghan Ireland
T: +353 (0)42 9692 333 **E:** info@bauder.ie
bauder.ie