

Declaration of Performance

BauderBIT R 333 BS

DoP-No.: 7831 0000



1.	Unique identification code of the product-type	BauderBIT R 333 BS - 1_01
2.	Intended use/es	Bitumen damp proof sheets including bitumen basement tanking sheets
3.	Manufacturer	Paul Bauder GmbH & Co. KG, Korntaler Landstrasse 63, 70499 Stuttgart, Germany
4.	System/s of assessment and verification of constancy of performance of the construction product	System 2+
5.	Harmonised standard Notified body	EN 13969:2004 + A1:2006 GPB, 1724

6. Declared performance

Essential characteristics	Performance EN 13969:2004 + A1:2006
Reaction to fire	E
Watertightness	passed
Tensile properties: Max. tensile force length (N/50mm) Max. tensile force transverse (N/50mm) Elongation at max. tensile force length (%) Elongation at max. tensile force transverse (%)	≥250 ≥150 ≥2 ≥2
Resistance to static loading (kg)	NPD
Resistance to impact (mm)	NPD
Tear resistance length (N) Tear resistance transversal (N)	NPD NPD
Joint strength: Peel resistance (N/50mm) Shear resistance (N/50mm)	NPD NPD
Durability: Watertightness after artificial ageing Watertightness after exposure to chemicals after artificial ageing	NPD NPD
Flexibility at low temperature top (°C) Flexibility at low temperature bottom (°C)	≤0 ≤0
Hazardous substances a),b)	Passed, see 5.15 EN 13969:2004 + A1:2006

a) Product does not contain asbestos or tar

b) Because there is no European test method for leaching of the products, no statement can be made.

NPD = no performance declared

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mark Bauder, Managing Director
Stuttgart, 28.11.2022