

# Technical data sheet

## BauderPVC NA

### PVC seam activator



V2 22/11/2022

<b>Application fields</b>	Should be used for preparing seams of aged or heavily soiled Thermofol PVC. Membrane for hot air welding.	
<b>Colour</b>	clear	
<b>Article number</b>	6051 0025	

Characteristic	Unit	Value
<b>Chemical base</b>	-	Solvent mixture on acetone basis
<b>Product storage</b>	-	store closed and cool
<b>Flash point</b>	°C	99
<b>Density</b>	g/m <sup>3</sup>	1.095
<b>Viscosity</b>	-	thin liquid
<b>Consumption</b>	-	30-60 g/lm seam depending on pollution
<b>Reaction to fire</b>	-	No hazardous goods
<b>Health risk</b>	-	No hazardous goods
<b>Package size</b>	-	2,5 l
<b>External fire performance</b>	-	not applicable

<b>Installation guidance</b>	It is not suitable as a general-purpose cleaner to remove dirt or bitumen residue from Thermofol membrane; Bauder PVC Cleaner is the recommended product for those requirements.
<b>Handling/PPE</b>	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using/handling the product, installers should be provided with, and wear, suitable personal protective equipment.
<b>Further information/documents</b>	Current documents such as DoC's, DoP's (where relevant), brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>
<b>Safety Data Sheet</b>	Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as a substance/mixture; therefore, this product does have a requirement for a Safety Data Sheet.