

TECHNICAL DATA SHEET

BauderTEC KSD Vapour Barrier

DESCRIPTION

A technically advanced self-adhesive elastomeric bitumen vapour barrier with an aluminium foil facing for vapour impermeability. The product will require the use of Bauder Self Adhesive primer, please check with Bauder Technical department for product details.

The product benefits from cleaner, safer and faster installation than traditional torch applied membranes.

TECHNICAL DATA:

Weights and sizes

Roll width	1 metre
Roll length	15 metres
Thickness:	1.5mm
Weight:	1.8Kg/m ²
Reinforcement:	60g/m ² glass fleece

Surface finishes

Top:	Aluminium foil
Bottom:	peel off release film covering self-adhesive bitumen

Technical performance

Tensile strength:	length	≥ 400N/50mm
	diagonal	≥ 400N/50mm

Cold bending test:	-30°C
Softening point:	+100°C

Shelf life 9 months from date of manufacture



UNITED KINGDOM

Bauder Ltd
70 Landseer Road
Ipswich Suffolk England IP3 0DH
T: +44 (0)1473 257671 **E:** info@bauder.co.uk
bauder.co.uk

IRELAND

Bauder Ltd
O'Duffy Centre Cross Lane Carrickmacross
Co. Monaghan Ireland
T: +353 (0)42 9692 333 **E:** info@bauder.ie
bauder.ie