

## Bauder PVC Lightning Conductor Clips

18.04.2023

|                            |   |
|----------------------------|---|
| <b>Product description</b> | A specialist lightning conductor clip riveted (carbon steel rivet) to a Bauder Thermofol PVC membrane base. Available in three colours.   |
| <b>Application fields</b>  | To be used with coated (25mm x 6mm) and un-coated (25mm x 3mm) lightning conductor tape in conjunction with Bauder Thermofol waterproofing systems.<br><b>Must be installed by Bauder Approved Contractors.</b> |
| <b>Article Number</b>      | GB12202010 (Light Grey)<br>GB12202030 (Blue Grey)<br>GB12202050 (Anthracite)  |



| Characteristic                 | Unit | Value   |
|--------------------------------|------|---|
| Length                         | mm   | 100   |
| Width                          | mm   | 100   |
| Thickness                      | mm   | 1.5   |
| Central block on membrane base | mm   | 20 (length) x 60 (width) x 23 (depth)                                   |
| Quantity                       | box  | 50  |
| Installation centres           | mm   | 500 - please consult with lightning conductor engineer for confirmation |

|                                       |   |
|---------------------------------------|---|
| <b>Storage guidance</b>               | The product should be stored in dry premises, protected against weathering, and must not be exposed to temperatures exceeding 35°C.   |
| <b>Packaging material</b>             | All products are supplied loose in a cardboard box (readily recyclable).  |
| <b>Handling/PPE</b>                   | All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment. |
| <b>Disposal guidance</b>              | Disposing of any waste material must be carried out in accordance with national regulations.<br>Recommended EWC waste codes:<br>17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03.              |
| <b>Further information/ documents</b> | Current documents such as brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>  |

### International Standards Organisation (ISO)

**ISO 9001:2015 Quality Management**  
Certificates EN1271 (UK)

**ISO 14001:2015 Environmental Management Certificates**  
A10552 (UK)


### Installation Guidance:

Mark out the location for the lightning conductor tape with a chalk line. Coated lightning conductor tape is often coated with an FPO coating therefore avoid intimate contact with the Thermofol membrane  
Weld the Lightning Conductor Clip to the Thermofol membrane at 500mm centres or at centres detailed by the installer of the lightning protection system. Install the lightning conductor tape. Close the clip and snap tight to secure.


### MEMBRANE COLOURS



Light Grey  
RAL 7035



Blue Grey  
RAL 7031



Anthracite  
RAL 7016

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.