

TECHNICAL DATA SHEET

Bauder LiquiTEC System

LiquiBALKON

DESCRIPTION

LiquiBALKON is a cold liquid applied fast curing waterproofing resin, for use on the main flat area of the LiquiTEC Reinforced Balcony, Walkway & Terrace system, beneath the LiquiPAVE RF Deck Floor Layer or other landscaping elements. It is applied in 2 coats 'wet-on-wet', with a layer of 110g Reinforcement fleece between. The product is a PMMA based resin and requires the addition of catalyst to trigger curing. It is solvent, isocyanate and halogen free, minimizing its environmental impact.

TECHNICAL DATA:

Colour:	Pebble grey (Approx.RAL 7032)
Coverage:	Minimum 3 Kg/m ²
Pack size:	10Kg re-sealable drum
Application temperature:	0°C to 35°C
Application method:	Roller
Rainproof time:	30 minutes approx.
Overcoat / traffic time:	45 minutes approx.

UNITED KINGDOM

Bauder Ltd

70 Landseer Road

Ipswich Suffolk England IP3 0DH

T: +44 (0)1473 257671 **E:** info@bauder.co.uk

bauder.co.uk

IRELAND

Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross

Co. Monaghan Ireland

T: +353 (0)42 9692 333 **E:** info@bauder.ie

bauder.ie