

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

* Commercial Product Name **Triflex Primer 610**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses base coat

Recommended restrictions Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Address Triflex GmbH & Co. KG
Karlstraße 59
D-32423 Minden
Telephone: +49 (0) 571 / 3 87 80 - 0
FAX: +49 (0) 571 / 3 87 80 - 738

IMPORTER AT:

Triflex GesmbH
Gessenschwand 39
4882 Oberwang
Oesterreich
Tel: +43 6233/20089
Fax: +43 6233/20089-10

IMPORTER B:

Triflex BVBA
Diamantstraat 6c
2200 Herentals
Belgie
Tel: +32 14 75 2550
Fax: +32 14 75 2614

IMPORTER CH:

Triflex GmbH
Hauptstrasse 36
6260 Reiden
Schweiz
Tel: +41 62 842 98 22
Fax +41 62 842 98 23

IMPORTER GB:

Triflex (UK) Ltd.
Whitebridge Way
STONE, STAFFORDSHIRE ST15 8JS
Great Britain
Fon: +44 1785 819119
Fax: +44 1785 819960

IMPORTER NL:

Triflex BV
Postbus 40128
8004 DC Zwolle
Nederland
Tel: +31 38 4602050
Fax: +31 38 4603857

IMPORTER PL:

Follmann Chemia Polska Sp.z.o.o. Ltd.
ul.Wypianskiego 43
60-751 Poznan
Poland
Tel: +48 616 683 445
Fax: +48 616 683 446

IMPORTER RUS:

OOO Follmann
140304 Moscow Geb.,
Kasimovskoje Schosse 36
Russian Federation
Tel: +43 6233/20089
Fax: +43 6233/20089-10

Responsible Department Environmental Department +49 (571) 9339-176

E-mail (competent person) sicherheitsdatenblatt@triflex.de

1.4 Emergency telephone number

Emergency telephone number Outside USA: -001 703 527 3887 (D814)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regula- Flam. Liq. 3; H226 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315
tion (EC) No. 1272/2008 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304

Safety Data Sheet as per regulation (EC) 1907/2006

Triflex

Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

2.2 Label elements

Hazard pictogram



GHS02



GHS07



GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label

xylene , ethylbenzene

H-statement(s)

H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312+H332: Harmful in contact with skin or if inhaled
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure .

* P-statement(s)

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331: Do NOT induce vomiting.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P314: Get medical advice/attention if you feel unwell.
P337+P313: If eye irritation persists: Get medical advice/attention.

* Further information

EUH205: Contains epoxy constituents. May produce an allergic reaction.

* Special labelling for certain preparations

Contains epoxy constituents. See information supplied by the manufacturer.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization

Solvent mixture

Hazardous ingredients

Ingredient		Classification (EC) 1272/2008	Concentration
xylene	CAS No.: 1330-20-7 EC-No.: 215-535-7 Index-No.: 601-022-00-9 REACH No.: 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	75.0 – 80.0 % by weight
ethylbenzene	CAS No.: 100-41-4 EC-No.: 202-849-4 Index-No.: 601-023-00-4 REACH No.: 01-2119489370-35-XXXX	Flam. Liq. 2; H225 Acute Tox. 4 ; H332 STOT RE 2; H373 (hearingorgans) Asp. Tox. 1; H304	15.0 – 20.0 % by weight
toluene	CAS No.: 108-88-3 EC-No.: 203-625-9 Index-No.: 601-021-00-3 REACH No.: 01-2119471310-51-XXXX	Flam. Liq. 2; H225 Repr. 2; H361d Asp. Tox. 1; H304 STOT RE 2 ; H373 Skin Irrit. 2; H315 STOT SE 3; H336	0.1 – 1.0 % by weight

Safety Data Sheet as per regulation (EC) 1907/2006

Triflex

Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Move out of dangerous area. Take off all contaminated clothing immediately. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.
If inhaled	Move to fresh air. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
In case of skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation occurs, get medical advice/attention.
In case of eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO ₂), Foam, Water spray, Dry powder
------------------------------	--

Extinguishing media which must not be used for safety reasons	High volume water jet
---	-----------------------

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases	Vapours may form explosive mixtures with air. Provide sufficient air exchange and/or exhaust in work rooms. Fire will produce dense black smoke containing hazardous combustion products (see heading 10). Exposure to decomposition products may be a hazard to health.
---	---

5.3 Advice for firefighters

Special protective equipment for firefighting	In the event of fire, wear self-contained breathing apparatus.
Additional information on firefighting	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind. Use personal protective equipment.
----------------------	---

6.2 Environmental precautions

Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.
---------------------------	--

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean contaminated surface thoroughly.
-------------------------	---

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

Treat recovered material as described in the section "Disposal considerations".

6.4 Reference to other sections

Reference to other sections Disposal considerations See also section 13

6.5 Additional information

Other information Treat recovered material as described in the section "Disposal considerations".

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment.
Handle and open container with care. Avoid contact with skin and eyes.

Precautions Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Observe label precautions.

Advice on protection against fire and explosion Take precautionary measures against static discharges. Vapours may form explosive mixture with air. Use water spray to cool unopened containers.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container requirements Storage must be in accordance with the BetrSichV (Germany). Keep in a cool, well-ventilated place. Keep in an area equipped with solvent resistant flooring.
Keep in properly labelled containers. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

TRGS 510

3

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

xylene

Great Britain

Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value / ppm	Short-term exposure value / mg/m ³	Remarks	Source
50	220	100	441	Can be absorbed through the skin.	19

Source: 19 - EH40/2005 Workplace exposure limits (2011)

Europe

Long-term exposure value/ mg/m ³	Long-term exposure value/ ppm	Short-term exposure value / mg/m ³	Short-term exposure value / ppm	Note	Issuing date	Source
221	50	442	100	Skin	2000/39	24

Source: 24 - DIRECTIVE 2009/161/EU

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

DNEL

Value	Target group	Exposure route	Exposure frequency	Source
77 mg/m ³	Workers	inhale	Long term effects systemic Local	100
289 mg/m ³	Workers	inhale	Short-term effects systemic Local	100
174 mg/m ³	Workers	dermal	Short-term effects Local	100
174 mg/m ³	Consumers	inhale	Short-term effects Local + systemic	100
14,8 mg/m ³	Consumers	Inhalation	Long term effects systemic	100
1,6 mg/kg	Consumers	Oral	Long term effects systemic	100
108 mg/kg	Consumers	dermal	Long term effects systemic	100

Source: 100 - Company data

PNEC

Value	Exposure route	Source
0,327 mg/l	freshwater	100
12,46 mg/kg	freshwater sediment	100
2,31 mg/kg	Soil	100
6,58 mg/l	Waste water treatment	100

Source: 100 - Company data

ethylbenzene

Great Britain

Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value / ppm	Short-term exposure value / mg/m ³	Remarks	Source
100	441	125	552	Can be absorbed through the skin.	19

Source: 19 - EH40/2005 Workplace exposure limits (2011)

Europe

Long-term exposure value/ mg/m ³	Long-term exposure value/ ppm	Short-term exposure value / mg/m ³	Short-term exposure value / ppm	Note	Issuing date	Source
442	100	884	200	Skin	2000/39	24

Source: 24 - DIRECTIVE 2009/161/EU

DNEL

Value	Target group	Exposure route	Exposure frequency	Source
77 mg/m ³	Workers	Inhalation	Long term effects systemic	100
180 mg/kg	Workers	dermal exposure	Long term effects systemic	100

Source: 100 - Company data

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

PNEC

Value	Exposure route	Source
0,1 mg/l	freshwater	100
0,01 mg/l	marine water	100
0,1 mg/l	Continuous release.	100
9,6 mg/l	Waste water pretreatment	100
13,7 mg/kg	freshwater sediment	100
1,37 mg/kg	marine sediment	100
2,68 mg/kg	Soil	100

Source: 100 - Company data

toluene

Great Britain

Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Remarks	Source
50	191	100	384	Can be absorbed through the skin.	19

Source: 19 - EH40/2005 Workplace exposure limits (2011)

Europe

Long-term exposure value/ mg/m3	Long-term exposure value/ ppm	Short-term exposure value / mg/m3	Short-term exposure value / ppm	Note	Issuing date	Source
192	50	384	100	Skin	2006/15	24

Source: 24 - DIRECTIVE 2009/161/EU

DNEL

Value	Target group	Exposure route	Exposure frequency	Source
192 mg/m ³	Workers	inhale	Long term effects systemic Local	100
384 mg/m ³	Workers	inhale	Acute systemic Local	100
384 mg/kg	Workers	dermal	Long term effects systemic	100
56,5 mg/m ³	Consumers	inhale	Local systemic	100
226 mg/m ³	Consumers	inhale	Acute systemic Local	100
226 mg/cm ²	Consumers	dermal	Long term effects systemic	100
8,13 mg/kg	Consumers	Oral	Long term effects systemic	100

Source: 100 - Company data

PNEC

Value	Exposure route	Source
0,68 mg/l	freshwater	100
0,68 mg/l	marine water	100
16,39 mg/l	freshwater sediment	100
16,39 mg/kg	marine sediment	100
13,61 mg/l	Waste water treatment	100
2,89 mg/kg	Soil	100

Source: 100 - Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Triflex

Commercial Product Name: **Triflex Primer 610**

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

8.2 Exposure controls

Respiratory protection	Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Remarks:	Recommended Filter type: A2 Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Hand protection	Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Unsuitable material:	woven fabric, Leather gloves
Suitable material:	Nitriles
Material thickness:	0,38 mm
Break through time:	<25 min
Eye protection	Tightly fitting safety goggles
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. Use protective skin cream before handling the product. Avoid contact with the skin and the eyes.
Engineering measures	Ensure adequate ventilation, especially in confined areas. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	Liquid
Colour	yellowish
Odour	solvent
Boiling point [°C]	appr.138 °C
Flash point [°C]	25-30 °C
Evaporation rate [kg/(s*m ²)]	not determined
Explosion limits [Vol-%]	
Lower limit:	1,7 % vol
Upper limit:	7,5 % vol
Vapour pressure [kPa]	1,0 kPa
Temperature:	20 °C
Vapour density	not determined
Density [g/cm ³]	appr.0,87 g/cm ³
Temperature:	20 °C

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

Water solubility [g/l]

Remarks: immiscible

Partition coefficient n-octanol /water (log P O/W) not determined

Autoignition temperature [°C] not determined

Viscosity, dynamic [kg/(m*s)] approx.4 – 7 mPa.s

Temperature: 20 °C

Explosive properties In use, may form flammable/explosive vapour-air mixture.

Oxidising properties Not relevant

9.2 Other information

Ignition temperature [°C] >450 °C

SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions Risk of violent reaction.

10.4 Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid Strong oxidizing agents, Strong acids and strong bases, Alkali metals

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Hazardous ingredients

xylene

Oral toxicity [mg/kg]	Test criterion	Test species	Source
>3523 mg/kg	LD50	rat	100

Source: 100 - Company data

Dermal toxicity [mg/kg]	Test criterion	Remarks	Source
1100 mg/kg	LD50	Chemical Safety Assessment	100

Source: 100 - Company data

LC50 Inhalation 4h for gases [ppmV]	Test criterion	Test species	Source
5000 ppm	LC50	rat	100

Source: 100 - Company data

LC50 Inhalation 4h for vapours [mg/l]	Test criterion	Test species	Exposure duration	Source
11 mg/l	LC50	rat	4 h	100

Source: 100 - Company data

Irritant effect on skin irritating

Irritant effect on eyes irritating Causes serious eye irritation.

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

Sensitization negative

Dermal absorption data Dermal absorption possible

Specific target organ toxicity (single exposure) [mg/kg]	Source
Causes respiratory tract irritation.	100

Source: 100 - Company data

ethylbenzene

Oral toxicity [mg/kg]	Test criterion	Test species	Source
> 3500 mg/kg	LD50	rat	100

Source: 100 - Company data

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
15400 mg/kg	LD50	rat	100

Source: 100 - Company data

Inhalative toxicity [mg/l]	Test criterion	Test species	Source
17,65 mg/l	LC0	rat	100

Source: 100 - Company data

LC50 Inhalation 4h for vapours [mg/l]	Source
17,65 mg/l	100

Source: 100 - Company data

Irritant effect on skin Mild skin irritation

Irritant effect on eyes weakly

Dermal absorption data Dermal absorption possible Solvents may degrease the skin.

toluene

Oral toxicity [mg/kg]	Test criterion	Test species	Source
5000 mg/kg	LD50	rat	100

Source: 100 - Company data

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
12124 mg/kg	LD50	rabbit	100

Source: 100 - Company data

LC50 Inhalation 4h for vapours [mg/l]	Test criterion	Test species	Exposure duration	Source
31 mg/l	LC50	rat	4 h	100

Source: 100 - Company data

11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes, respiratory system and skin. Irritating to mucous membranes

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

SECTION 12: Ecological information

12.1 Toxicity

Hazardous ingredients

xylene

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
2,6 mg/l	LC50	Oncorhynchus mykiss (rainbow trout)	96 h	100

Source: 100 - Company data

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
1,1 mg/l	EC 50	Daphnia magna (Water flea)	48 h	100

Source: 100 - Company data

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Source
2,2 mg/l	ErC50	Algae (mg/l)	72 h	100

Source: 100 - Company data

Ready degradability

ethylbenzene

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
4,2 mg/l	LC50	Oncorhynchus mykiss (rainbow trout)	96 h	100

Source: 100 - Company data

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
1,8 mg/l	EC 50	Daphnia magna (Water flea)	48 h	100

Source: 100 - Company data

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Source
4,6 mg/l	EC 50	Selenastrum capricornutum (green algae)	72 h	100

Source: 100 - Company data

Ready degradability

toluene

Toxicity to fish [mg/l]	Test criterion	Source
5,5 mg/l	LC50	100

Source: 100 - Company data

Toxicity to daphnia [mg/l]	Test criterion	Source
3,78 mg/l	EC 50	100

Source: 100 - Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

Toxicity to algae [mg/l]	Test criterion	Exposure duration	Source
>433 mg/l	EC 50	96 h	100

Source: 100 - Company data

NOEC (fish) [mg/l]	Test species	Source
1,4 mg/l	Oncorhynchus mykiss (rainbow trout)	100

Source: 100 - Company data

NOEC (daphnia) [mg/l]	Test species	Source
(0,74)mg/l	Ceriodaphnia dubia	100

Source: 100 - Company data

Ready degradability

Bioaccumulation Does not bioaccumulate.

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

12.6 Other adverse effects

Further information on ecology See also section 12.1

SECTION 13: Disposal considerations




13.1 Waste treatment methods

Disposal considerations According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The following Waste Codes are only suggestions:

Waste Code 07 02 04* other organic solvents, washing liquids and mother liquors

Uncleaned empty packaging Die Rücknahme der Verpackungsmaterialien ist über das Interseroh System geregelt.

SECTION 14: Transport information

	Land transport ADR/RID	* Marine transport IMDG	* Air transport ICAO/IATA
14.1 UN-No	1307	1307	1307
14.2 Description of the goods	XYLENES	XYLENES	XYLENES
14.2 UN proper shipping name		XYLENES	Xylenes
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group	III	III	III
Labels	3 	3 	3 
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
Tunnel restriction code	D/E		
Name affix	solution	solution	solution
EmS		F-E;S-D	

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: Triflex Primer 610

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

	Land transport ADR/RID	* Marine transport IMDG	* Air transport ICAO/IATA
Stowage category		A	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC Code Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations Additionally, observe any national regulations!

Water Hazard Class (Ger.) 2

Classification in compliance with the Industrial Safety Regulation flammable

* GISCODE M-VM04

SECTION 16: Other information

Relevant H-phrases
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H361d: Suspected of damaging the unborn child.
H373: May cause damage to organs through prolonged or repeated exposure .
EUH205: Contains epoxy constituents. May produce an allergic reaction.

Wording of the hazard classes
Flam. Liq.: Flammable liquid
Acute Tox.: Acute toxicity
Skin Irrit.: Skin irritation
Eye Irrit.: Serious eye irritation
STOT SE: Specific target organ toxicity – single exposure
STOT RE: Specific target organ toxicity – repeated exposure
Asp. Tox.: Aspiration hazard
Repr.: Reproductive toxicity

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	evaluation
Flam. Liq. 3; H226	
Acute Tox. 4; H312	
Acute Tox. 4; H332	
Skin Irrit. 2; H315	
Eye Irrit. 2; H319	
STOT SE 3; H335	
STOT RE 2; H373	
Asp. Tox. 1; H304	

Department issuing safety data sheet Environmental Department

Recommended restrictions Reserved for industrial and professional use.

Modifications of the previous version are denoted with an asterisk (*).

Safety Data Sheet as per regulation (EC) 1907/2006

Triflex

Commercial Product Name: **Triflex Primer 610**

Article-No.: 24610-000

Revision Date: 24.08.2018

Version: 5.0 /en

Replaces version from: 14.09.2017

Print date: 26.02.2019

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.